NSN 5305-01-052-5807

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-052-5807 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.116 inches **Fastener Length:** 0.356 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.295 inches and 0.305 inches **Head Height:** 0.080 inches First Diameter From Head: Between 0.186 inches and 0.190 inches **Second Diameter From Head:** Between 0.174 inches and 0.177 inches Third Diameter From Head: Between 0.186 inches and 0.190 inches **Fourth Diameter From Head:** Between 0.083 inches and 0.093 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.157 inches and 0.167 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 0.173 inches and 0.187 inches **Distance From Largest Bearing Surface Of Head To End Of Third Diameter:** 0.200 inches Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter: 0.240 inches **Internal Drive Style:** Slot **End Application:** An/alq-131 block i **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 **Externally Relieved Body Diameter Quantity:**

Material:

Steel comp 303

NSN 5305-01-052-5807

Externally Relieved Body Screw - Page 2 of 2



Material Specification: Astm a582 cond a assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 type 2 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: --Demilitarization: No

Fiig: A003b0