Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-052-5807

Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
0.116 inches
Fastener Length:
0.356 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.295 inches and 0.305 inches
Head Height:
0.080 inches
First Diameter From Head:
Between 0.186 inches and 0.190 inches
Second Diameter From Head:
Between 0.174 inches and 0.177 inches
Third Diameter From Head:
Between 0.186 inches and 0.190 inches
Fourth Diameter From Head:
Between 0.083 inches and 0.093 inches
Distance From Largest Bearing Surface Of Head To End Of First Diameter:
Between 0.157 inches and 0.167 inches
Distance From Largest Bearing Surface Of Head To End Of Second Diameter:
Between 0.173 inches and 0.187 inches
Distance From Largest Bearing Surface Of Head To End Of Third Diameter:
0.200 inches
Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter:
0.240 inches
Internal Drive Style:
Slot
End Application:
An/alq-131 block i
Thread Diameter:
0.138 inches
Thready Qty Per Inch (tpi):
32
Externally Relieved Body Diameter Quantity:
4
Material:
Steel comp 303



Material Specification: Astm a582 cond a assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 type 2 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A003b0