NSN 5305-01-052-5808

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-052-5808 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.258 inches and 0.262 inches **Fastener Length:** Between 0.418 inches and 0.422 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.555 inches and 0.565 inches **Head Height:** Between 0.058 inches and 0.062 inches **First Diameter From Head:** Between 0.306 inches and 0.316 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.160 inches **Internal Drive Style:** Slot **End Application:** An/alq-131 block i **Thread Diameter:** 0.375 inches Thready Qty Per Inch (tpi): 24 **Externally Relieved Body Diameter Quantity: Special Features:** Hole threaded end 0.360 in. Deep, 0.250 in. Dia Material: Steel comp 303 **Material Specification:** Qq-s-764 cond a federal specification single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 type 2 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life:

N/a

NSN 5305-01-052-5808

Externally Relieved Body Screw - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0