
NSN 5305-01-052-9815

Close Tolerance Screw - Page 1 of 2





Thread Class: 3a **Thread Direction: Right-hand Thread Length:** Between 0.413 inches and 0.463 inches Fastener Length: Between 1.048 inches and 1.078 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.573 inches and 0.635 inches **Grip Diameter:** Between 0.3110 inches and 0.3120 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.312 inches Grip Length: Between 0.615 inches and 0.635 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 220000 pounds per square inch Hardness Rating: 46.0 rockwell c and 49.0 rockwell c **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Steel comp h11 **Material Specification:** Ams 6487 assn standard single material response Surface Treatment: Cadmium Surface Treatment Specification: Nas 672 assn standard single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a Unit Of Measure:

NSN 5305-01-052-9815

Close Tolerance Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

