## NSN 5305-01-053-1885

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-053-1885

Thread Class:				
3a				
Thread Direction:				
Right-hand				
Thread Length:				
1.750 inches				
Fastener Length:				
Between 2.156 inches and 2.250 inches				
Head Style:				
Pan				
Head Diameter:				
Between 0.306 inches and 0.322 inches				
Head Height:				
Between 0.105 inches and 0.115 inches				
Locking Feature:				
Strip threads				
Internal Drive Style:				
Cross recess type 1				
Thread Diameter:				
0.164 inches				
Thready Qty Per Inch (tpi):				
32				
Min. Tensile Strength (psi):				
160000 pounds per square inch				
Hardness Rating:				
36.0 rockwell c and 40.0 rockwell c				
Surface Finish:				
32.0 microinches threads				
Material:				
Steel comp 4140 fastener or steel comp 4340 fastener or steel comp 8740 fastener				
Material Specification:				
Mil-s-5626 military specification 1st material response fastener or mil-s-8844 military specification 2nd material response fastener or				
ams6414 assn standard 2nd material response fastener or mil-s-6049 military specification 3rd material response fastener				
Surface Treatment:				
Cadmium fastener and chromate fastener				
Surface Treatment Specification:				
Qq-p-416 ty2 cl2 federal specification single treatment response				
Thread Series Designator:				
Unjc				
Specification Data:				
80205-nas1190 professional/industrial association standard				
Shelf Life:				

N/a

## NSN 5305-01-053-1885

Socket Head Cap Screw - Page 2 of 2



П	Init	7 1+	Measure:
u	,,,,,	v	wicasuic.

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.