NSN 5305-01-053-1900

Hexagon Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-053-1900

Thread Direction: Right-hand Thread Length: Between 1.000 inches and 1.188 inches Fastener Length: Between 2.156 inches and 2.250 inches Head Style: Hexagon Head Height: Between 0.226 inches and 0.243 inches Width Between Flats: Between 0.551 inches and 0.562 inches Hole Diameter: 0.062 inches Thread Diameter: 0.375 inches Hole Quantity: 1 Hole Type: Drilled Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 70000 pounds per square inch Hardness Rating: 235.0 brinell standard Minimum Yield Strength: 40000 pounds per square inch Hole Configuration Style: Hexagon flats Material: Steel comp 410 or steel comp 416 or steel comp 430 Material Specification: 66 federal standard all material responses	Thread Class:
Right-hand Thread Length: Between 1.000 inches and 1.188 inches Fastener Length: Between 2.156 inches and 2.250 inches Head Style: Hexagon Head Height: Between 0.226 inches and 0.243 inches Width Between Flats: Between 0.551 inches and 0.562 inches Hole Diameter: 0.062 inches Thread Diameter: 0.375 inches Hole Quantity: 1 Hole Type: Drilled Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 70000 pounds per square inch Hardness Rating: 235.0 brinell standard Minimum Yield Strength: 40000 pounds per square inch Hole Configuration Style: Hexagon flats Material: Steel comp 410 or steel comp 416 or steel comp 430 Material Specification: 66 federal standard all material responses	2a
Thread Length: Between 1.000 inches and 1.188 inches Fastener Length: Between 2.156 inches and 2.250 inches Head Style: Hexagon Head Height: Between 0.226 inches and 0.243 inches Width Between Flats: Between 0.551 inches and 0.562 inches Hole Diameter: 0.062 inches Thread Diameter: 0.375 inches Hole Quantity: 1 Hole Type: Drilled Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 70000 pounds per square inch Hardness Rating: 235.0 brinell standard Minimum Yield Strength: 40000 pounds per square inch Hole Configuration Style: Hexagon flats Material: Steel comp 410 or steel comp 416 or steel comp 430 Material Specification: 66 federal standard all material responses	Thread Direction:
Between 1.000 inches and 1.188 inches Fastener Length: Between 2.156 inches and 2.250 inches Head Style: Hexagon Head Height: Between 0.226 inches and 0.243 inches Width Between Flats: Between 0.551 inches and 0.562 inches Hole Diameter: 0.062 inches Thread Diameter: 0.375 inches Hole Quantity: 1 Hole Type: Drilled Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 70000 pounds per square inch Hardness Rating: 235.0 brinell standard Minimum Yield Strength: 40000 pounds per square inch Hole Configuration Style: Hexagon flats Material: Steel comp 410 or steel comp 416 or steel comp 430 Material Specification: 66 federal standard all material responses	Right-hand
Fastener Length: Between 2.156 inches and 2.250 inches Head Style: Hexagon Head Height: Between 0.226 inches and 0.243 inches Width Between Flats: Between 0.551 inches and 0.562 inches Hole Diameter: 0.062 inches Thread Diameter: 0.375 inches Hole Quantity: 1 Hole Type: Drilled Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 70000 pounds per square inch Hardness Rating: 235.0 brinell standard Minimum Yield Strength: 40000 pounds per square inch Hole Configuration Style: Hexagon flats Material: Steel comp 410 or steel comp 416 or steel comp 430 Material Specification: 66 federal standard all material responses	Thread Length:
Between 2.156 inches and 2.250 inches Head Style: Hexagon Head Height: Between 0.226 inches and 0.243 inches Width Between Flats: Between 0.551 inches and 0.562 inches Hole Diameter: 0.062 inches Thread Diameter: 0.375 inches Hole Quantity: 1 Hole Type: Drilled Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 70000 pounds per square inch Hardness Rating: 235.0 brinell standard Minimum Yield Strength: 40000 pounds per square inch Hole Configuration Style: Hexagon flats Material: Steel comp 410 or steel comp 416 or steel comp 430 Material Specification: 66 federal standard all material responses	Between 1.000 inches and 1.188 inches
Head Style: Hexagon Head Height: Between 0.226 inches and 0.243 inches Width Between Flats: Between 0.551 inches and 0.562 inches Hole Diameter: 0.062 inches Thread Diameter: 0.375 inches Hole Quantity: 1 Hole Type: Drilled Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 70000 pounds per square inch Hardness Rating: 235.0 brinell standard Minimum Yield Strength: 40000 pounds per square inch Hole Configuration Style: Hexagon flats Material: Steel comp 410 or steel comp 416 or steel comp 430 Material Specification: 66 federal standard all material responses	Fastener Length:
Hexagon Head Height: Between 0.226 inches and 0.243 inches Width Between Flats: Between 0.551 inches and 0.562 inches Hole Diameter: 0.062 inches Thread Diameter: 0.375 inches Hole Quantity: 1 Hole Type: Drilled Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 70000 pounds per square inch Hardness Rating: 235.0 brinell standard Minimum Yield Strength: 40000 pounds per square inch Hole Configuration Style: Hexagon flats Material: Steel comp 410 or steel comp 416 or steel comp 430 Material Specification: 66 federal standard all material responses	Between 2.156 inches and 2.250 inches
Head Height: Between 0.226 inches and 0.243 inches Width Between Flats: Between 0.551 inches and 0.562 inches Hole Diameter: 0.062 inches Thread Diameter: 0.375 inches Hole Quantity: 1 Hole Type: Drilled Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 70000 pounds per square inch Hardness Rating: 235.0 brinell standard Minimum Yield Strength: 40000 pounds per square inch Hole Configuration Style: Hexagon flats Material: Steel comp 410 or steel comp 416 or steel comp 430 Material Specification: 66 federal standard all material responses	Head Style:
Between 0.226 inches and 0.243 inches Width Between Flats: Between 0.551 inches and 0.562 inches Hole Diameter: 0.062 inches Thread Diameter: 0.375 inches Hole Quantity: 1 Hole Type: Drilled Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 70000 pounds per square inch Hardness Rating: 235.0 brinell standard Minimum Yield Strength: 40000 pounds per square inch Hole Configuration Style: Hexagon flats Material: Steel comp 410 or steel comp 416 or steel comp 430 Material Specification: 66 federal standard all material responses	Hexagon
Width Between Flats: Between 0.551 inches and 0.562 inches Hole Diameter: 0.062 inches Thread Diameter: 0.375 inches Hole Quantity: 1 Hole Type: Drilled Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 70000 pounds per square inch Hardness Rating: 235.0 brinell standard Minimum Yield Strength: 40000 pounds per square inch Hole Configuration Style: Hexagon flats Material: Steel comp 410 or steel comp 416 or steel comp 430 Material Specification: 66 federal standard all material responses	Head Height:
Between 0.551 inches and 0.562 inches Hole Diameter: 0.062 inches Thread Diameter: 0.375 inches Hole Quantity: 1 Hole Type: Drilled Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 70000 pounds per square inch Hardness Rating: 235.0 brinell standard Minimum Yield Strength: 40000 pounds per square inch Hole Configuration Style: Hexagon flats Material: Steel comp 410 or steel comp 416 or steel comp 430 Material Specification: 66 federal standard all material responses	Between 0.226 inches and 0.243 inches
Hole Diameter: 0.062 inches Thread Diameter: 0.375 inches Hole Quantity: 1 Hole Type: Drilled Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 70000 pounds per square inch Hardness Rating: 235.0 brinell standard Minimum Yield Strength: 40000 pounds per square inch Hole Configuration Style: Hexagon flats Material: Steel comp 410 or steel comp 416 or steel comp 430 Material Specification: 66 federal standard all material responses	Width Between Flats:
O.062 inches Thread Diameter: O.375 inches Hole Quantity: 1 Hole Type: Drilled Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 70000 pounds per square inch Hardness Rating: 235.0 brinell standard Minimum Yield Strength: 40000 pounds per square inch Hole Configuration Style: Hexagon flats Material: Steel comp 410 or steel comp 416 or steel comp 430 Material Specification: 66 federal standard all material responses	Between 0.551 inches and 0.562 inches
Thread Diameter: 0.375 inches Hole Quantity: 1 Hole Type: Drilled Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 70000 pounds per square inch Hardness Rating: 235.0 brinell standard Minimum Yield Strength: 40000 pounds per square inch Hole Configuration Style: Hexagon flats Material: Steel comp 410 or steel comp 416 or steel comp 430 Material Specification: 66 federal standard all material responses	Hole Diameter:
0.375 inches Hole Quantity: 1 Hole Type: Drilled Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 70000 pounds per square inch Hardness Rating: 235.0 brinell standard Minimum Yield Strength: 40000 pounds per square inch Hole Configuration Style: Hexagon flats Material: Steel comp 410 or steel comp 416 or steel comp 430 Material Specification: 66 federal standard all material responses	0.062 inches
Hole Quantity: 1 Hole Type: Drilled Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 70000 pounds per square inch Hardness Rating: 235.0 brinell standard Minimum Yield Strength: 40000 pounds per square inch Hole Configuration Style: Hexagon flats Material: Steel comp 410 or steel comp 416 or steel comp 430 Material Specification: 66 federal standard all material responses	Thread Diameter:
Hole Type: Drilled Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 70000 pounds per square inch Hardness Rating: 235.0 brinell standard Minimum Yield Strength: 40000 pounds per square inch Hole Configuration Style: Hexagon flats Material: Steel comp 410 or steel comp 416 or steel comp 430 Material Specification: 66 federal standard all material responses	0.375 inches
Hole Type: Drilled Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 70000 pounds per square inch Hardness Rating: 235.0 brinell standard Minimum Yield Strength: 40000 pounds per square inch Hole Configuration Style: Hexagon flats Material: Steel comp 410 or steel comp 416 or steel comp 430 Material Specification: 66 federal standard all material responses	Hole Quantity:
Drilled Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 70000 pounds per square inch Hardness Rating: 235.0 brinell standard Minimum Yield Strength: 40000 pounds per square inch Hole Configuration Style: Hexagon flats Material: Steel comp 410 or steel comp 416 or steel comp 430 Material Specification: 66 federal standard all material responses	1
Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 70000 pounds per square inch Hardness Rating: 235.0 brinell standard Minimum Yield Strength: 40000 pounds per square inch Hole Configuration Style: Hexagon flats Material: Steel comp 410 or steel comp 416 or steel comp 430 Material Specification: 66 federal standard all material responses	Hole Type:
Min. Tensile Strength (psi): 70000 pounds per square inch Hardness Rating: 235.0 brinell standard Minimum Yield Strength: 40000 pounds per square inch Hole Configuration Style: Hexagon flats Material: Steel comp 410 or steel comp 416 or steel comp 430 Material Specification: 66 federal standard all material responses	Drilled
Min. Tensile Strength (psi): 70000 pounds per square inch Hardness Rating: 235.0 brinell standard Minimum Yield Strength: 40000 pounds per square inch Hole Configuration Style: Hexagon flats Material: Steel comp 410 or steel comp 416 or steel comp 430 Material Specification: 66 federal standard all material responses	Thready Qty Per Inch (tpi):
70000 pounds per square inch Hardness Rating: 235.0 brinell standard Minimum Yield Strength: 40000 pounds per square inch Hole Configuration Style: Hexagon flats Material: Steel comp 410 or steel comp 416 or steel comp 430 Material Specification: 66 federal standard all material responses	16
Hardness Rating: 235.0 brinell standard Minimum Yield Strength: 40000 pounds per square inch Hole Configuration Style: Hexagon flats Material: Steel comp 410 or steel comp 416 or steel comp 430 Material Specification: 66 federal standard all material responses	Min. Tensile Strength (psi):
235.0 brinell standard Minimum Yield Strength: 40000 pounds per square inch Hole Configuration Style: Hexagon flats Material: Steel comp 410 or steel comp 416 or steel comp 430 Material Specification: 66 federal standard all material responses	70000 pounds per square inch
Minimum Yield Strength: 40000 pounds per square inch Hole Configuration Style: Hexagon flats Material: Steel comp 410 or steel comp 416 or steel comp 430 Material Specification: 66 federal standard all material responses	Hardness Rating:
40000 pounds per square inch Hole Configuration Style: Hexagon flats Material: Steel comp 410 or steel comp 416 or steel comp 430 Material Specification: 66 federal standard all material responses	235.0 brinell standard
Hole Configuration Style: Hexagon flats Material: Steel comp 410 or steel comp 416 or steel comp 430 Material Specification: 66 federal standard all material responses	Minimum Yield Strength:
Hexagon flats Material: Steel comp 410 or steel comp 416 or steel comp 430 Material Specification: 66 federal standard all material responses	40000 pounds per square inch
Material: Steel comp 410 or steel comp 416 or steel comp 430 Material Specification: 66 federal standard all material responses	Hole Configuration Style:
Steel comp 410 or steel comp 416 or steel comp 430 Material Specification: 66 federal standard all material responses	Hexagon flats
Material Specification: 66 federal standard all material responses	Material:
66 federal standard all material responses	Steel comp 410 or steel comp 416 or steel comp 430
	Material Specification:
Surface Treatment:	66 federal standard all material responses
Surface Treatment.	Surface Treatment:
Passivate	Passivate
Surface Treatment Specification:	Surface Treatment Specification:
Qq-p-35 federal specification single treatment response	

Unc

Thread Series Designator:

NSN 5305-01-053-1900

Hexagon Head Cap Screw - Page 2 of 2



2 type and 10p style

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0