NSN 5305-01-053-9784



Shoulder Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-053-9784 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.422 inches and 0.442 inches **Fastener Length:** Between 0.923 inches and 0.933 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.419 inches and 0.437 inches **Head Height:** Between 0.209 inches and 0.219 inches **Shoulder Diameter:** 0.309 inches first shoulder and 0.311 inches first shoulder **Shoulder Length:** 0.491 inches first shoulder and 0.501 inches first shoulder **Internal Drive Style:** Hexagon **Thread Diameter:** 0.250 inches Width Across Flats: 0.156 inches Thready Qty Per Inch (tpi): 20 **Shoulder Shape:** Round first shoulder Material: Steel comp 4037 **Material Specification:** Mil-s-21472 military specification single material response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

Demilitarization: No

Fiig:

A003b0

NSN 5305-01-053-9784

Shoulder Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-21472 spec.