NSN 5305-01-054-2299



Shoulder Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-054-2299 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.469 inches **Fastener Length:** Between 2.079 inches and 2.109 inches **Head Style:** Hexagon **Head Height:** Between 0.203 inches and 0.235 inches Width Between Flats: Between 0.553 inches and 0.564 inches **Shoulder Diameter:** 0.3740 inches first shoulder and 0.3745 inches first shoulder **Shoulder Length:** 1.625 inches first shoulder and 1.645 inches first shoulder **Shoulder Width Across Flats:** 0.547 inches first shoulder **Internal Drive Style:** W/o internal drive **Thread Diameter:** 0.312 inches Thready Qty Per Inch (tpi): 24 **Shoulder Shape:** Round first shoulder Material: Steel comp e4340 or steel comp 8740 **Material Specification:** Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams 6322 assn standard 2nd material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 type 2 class 3 federal specification single treatment response **Thread Series Designator:** Unjf

--

N/a

Shelf Life:

Unit Of Measure:

NSN 5305-01-054-2299

Shoulder Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.