## NSN 5305-01-054-4633

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-054-4633 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.400 inches and 0.450 inches **Fastener Length:** Between 1.972 inches and 2.002 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.455 inches and 0.510 inches **Grip Diameter:** Between 0.2485 inches and 0.2495 inches **Internal Drive Style:** Cross recess type 1 **End Application:** Aircraft, stratolifter c-135; e-3a awacs; joint stars target radar sys **Thread Diameter:** 0.250 inches **Grip Length:** Between 1.552 inches and 1.572 inches Thready Qty Per Inch (tpi): 28 **Countersink Angle:** 100.0 degrees **Surface Finish:** 32.0 microinches threads Material: Steel comp e4340 or steel comp 4340 or steel comp 8740 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, class 3 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** No

## NSN 5305-01-054-4633

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0