
## NSN 5305-01-054-5421

Close Tolerance Screw - Page 1 of 2





**Thread Class:** 3a **Thread Direction: Right-hand Thread Length:** Between 0.378 inches and 0.428 inches Fastener Length: Between 1.326 inches and 1.356 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.350 inches and 0.399 inches **Grip Diameter:** Between 0.2485 inches and 0.2495 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.250 inches Grip Length: Between 0.928 inches and 0.948 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 220000 pounds per square inch Hardness Rating: 46.0 rockwell c and 49.0 rockwell c **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Steel comp h11 **Material Specification:** Ams 6487 assn standard single material response Surface Treatment: Cadmium Surface Treatment Specification: Nas 672 assn standard single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a Unit Of Measure:

---

## NSN 5305-01-054-5421

Close Tolerance Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

