NSN 5305-01-054-6252

Close Tolerance Screw - Page 1 of 2

3a





Thread Class: Thread Direction: Right-hand Thread Length: Between 0.668 inches and 0.698 inches Fastener Length: 3.358 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.605 inches and 0.625 inches **Head Height:** Between 0.112 inches and 0.125 inches **Grip Diameter:** Between 0.4360 inches and 0.4370 inches **Internal Drive Style:** Offset cruciform (torque set) **End Application:** Aircraft, f-16 **Thread Diameter:** 0.438 inches Grip Length: Between 2.665 inches and 2.685 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 220000 pounds per square inch Surface Finish: 32.0 microinches threads **Special Features:** Conical bearing surface of head 99.0 degree to 101.0 degree included angle 0.077 in. Long Material: Steel comp h11 **Material Specification:** Ams 6487 assn standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Nas 672 assn standard single treatment response

Thread Series Designator:

Unjf

20

NSN 5305-01-054-6252

Close Tolerance Screw - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

