NSN 5305-01-054-6262

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-054-6262 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.338 inches and 0.388 inches **Fastener Length:** Between 0.786 inches and 0.816 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.258 inches and 0.305 inches **Grip Diameter:** Between 0.1885 inches and 0.1895 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.190 inches **Grip Length:** Between 0.428 inches and 0.448 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 220000 pounds per square inch Hardness Rating: 46.0 rockwell c and 49.0 rockwell c **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Steel comp h11 **Material Specification:** Ams 6487 assn standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Nas 672 assn standard single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

--

Unit Of Measure:

NSN 5305-01-054-6262

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0