NSN 5305-01-054-6264

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-054-6264

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.378 inches and 0.428 inches
Fastener Length:
Between 1.076 inches and 1.106 inches
Head Style: Flat countersunk
Head Diameter:
Between 0.350 inches and 0.399 inches
Grip Diameter:
Between 0.2485 inches and 0.2495 inches
Internal Drive Style:
Offset cruciform (torque set)
Thread Diameter:
0.250 inches
Grip Length:
Between 0.678 inches and 0.698 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
220000 pounds per square inch
220000 pounds per square inch Hardness Rating:
220000 pounds per square inch Hardness Rating: 46.0 rockwell c and 49.0 rockwell c
220000 pounds per square inch Hardness Rating: 46.0 rockwell c and 49.0 rockwell c Countersink Angle:
 220000 pounds per square inch Hardness Rating: 46.0 rockwell c and 49.0 rockwell c Countersink Angle: Between 99.0 degrees and 101.0 degrees
220000 pounds per square inch Hardness Rating: 46.0 rockwell c and 49.0 rockwell c Countersink Angle: Between 99.0 degrees and 101.0 degrees Material:
220000 pounds per square inch Hardness Rating: 46.0 rockwell c and 49.0 rockwell c Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Steel comp h11
220000 pounds per square inch Hardness Rating: 46.0 rockwell c and 49.0 rockwell c Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Steel comp h11 Material Specification:
220000 pounds per square inch Hardness Rating: 46.0 rockwell c and 49.0 rockwell c Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Steel comp h11
220000 pounds per square inch Hardness Rating: 46.0 rockwell c and 49.0 rockwell c Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Steel comp h11 Material Specification:
220000 pounds per square inch Hardness Rating: 46.0 rockwell c and 49.0 rockwell c Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Steel comp h11 Material Specification: Ams 6487 assn standard single material response
220000 pounds per square inch Hardness Rating: 46.0 rockwell c and 49.0 rockwell c Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Steel comp h11 Material Specification: Ams 6487 assn standard single material response Surface Treatment:
220000 pounds per square inch Hardness Rating: 46.0 rockwell c and 49.0 rockwell c Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Steel comp h11 Material Specification: Ams 6487 assn standard single material response Surface Treatment: Cadmium
220000 pounds per square inch Hardness Rating: 46.0 rockwell c and 49.0 rockwell c Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Steel comp h11 Material Specification: Ams 6487 assn standard single material response Surface Treatment: Cadmium
220000 pounds per square inch Hardness Rating: 46.0 rockwell c and 49.0 rockwell c Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Steel comp h11 Material Specification: Ams 6487 assn standard single material response Surface Treatment: Cadmium Surface Treatment Specification: Nas 672 assn standard single treatment response
220000 pounds per square inch Hardness Rating: 46.0 rockwell c and 49.0 rockwell c Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Steel comp h11 Material Specification: Ams 6487 assn standard single material response Surface Treatment: Cadmium Surface Treatment Specification: Nas 672 assn standard single treatment response Thread Series Designator:
220000 pounds per square inch Hardness Rating: 46.0 rockwell c and 49.0 rockwell c Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Steel comp h11 Material Specification: Ams 6487 assn standard single material response Surface Treatment: Cadmium Surface Treatment Specification: Nas 672 assn standard single treatment response Thread Series Designator: Unjf
220000 pounds per square inch Hardness Rating: 46.0 rockwell c and 49.0 rockwell c Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Steel comp h11 Material Specification: Ams 6487 assn standard single material response Surface Treatment: Cadmium Surface Treatment Specification: Nas 672 assn standard single treatment response Thread Series Designator: Unjf Shelf Life:

NSN 5305-01-054-6264

Close Tolerance Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

