## NSN 5305-01-054-6268

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-054-6268 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.403 inches **Fastener Length:** Between 0.638 inches and 0.668 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.350 inches and 0.399 inches **Grip Diameter:** Between 0.2485 inches and 0.2495 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.250 inches **Grip Length:** Between 0.240 inches and 0.260 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 220000 pounds per square inch Hardness Rating: 46.0 rockwell c and 49.0 rockwell c **Countersink Angle:** 100.0 degrees Material: Steel **Material Specification:** Ams 6487 assn standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Nas 672 assn standard single treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a
Unit Of Measure:

## NSN 5305-01-054-6268

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0