NSN 5305-01-054-6283

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-054-6283

Thread Class:	
3a	
Thread Direction:	
Right-hand	
Thread Length:	
Between 0.644 inches and 0.674 inches	
Fastener Length:	
Between 1.582 inches and 1.612 inches	
Head Style:	
Flat countersunk	
Head Diameter:	
Between 0.717 inches and 0.760 inches	
Grip Diameter:	
Between 0.3735 inches and 0.3745 inches	
Internal Drive Style:	
Hexagon	
Thread Diameter:	
0.375 inches	
Grip Length:	
Between 0.928 inches and 0.948 inches	
Thready Qty Per Inch (tpi):	
24	
Min. Tensile Strength (psi):	
220000 pounds per square inch	
Hardness Rating:	
46.0 rockwell c and 49.0 rockwell c	
Countersink Angle:	
100.0 degrees	
Material:	
Steel	
Material Specification:	
Ams 6487 assn standard single material response	
Surface Treatment:	
Cadmium	
Surface Treatment Specification:	
Nas 672 assn standard single treatment response	
Thread Series Designator:	
Unjf	
Shelf Life:	
N/a	
Unit Of Measure:	
_	

NSN 5305-01-054-6283

Close Tolerance Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

