NSN 5305-01-054-6288

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-054-6288 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.298 inches and 0.348 inches **Fastener Length:** Between 0.933 inches and 0.963 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.325 inches and 0.385 inches **Grip Diameter:** Between 0.1885 inches and 0.1895 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.190 inches **Grip Length:** Between 0.615 inches and 0.635 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 220000 pounds per square inch Hardness Rating: 46.0 rockwell c and 49.0 rockwell c **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Steel comp h11 **Material Specification:** Ams 6487 assn standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Nas 672 assn standard single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

Unit Of Measure:

NSN 5305-01-054-6288

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0