NSN 5305-01-054-7351

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-054-7351 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.505 inches and 0.572 inches **Fastener Length:** Between 1.077 inches and 1.124 inches **Head Style:** Flat countersunk undercut **Head Diameter:** Between 0.629 inches and 0.633 inches **Head Height:** Between 0.088 inches and 0.090 inches **Grip Diameter:** Between 0.3110 inches and 0.3120 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.312 inches **Grip Length:** Between 0.552 inches and 0.572 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch **Hardness Rating:** 36.0 rockwell c and 40.0 rockwell c **Countersink Angle:** 100.0 degrees Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740 or steel comp 4130 **Surface Treatment:** Cadmium **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5305-01-054-7351

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0