

View Online at <https://aerobasegroup.com/nsn/5305-01-054-8398>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.318 inches and 0.368 inches

**Fastener Length:**

Between 1.140 inches and 1.170 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.355 inches and 0.397 inches

**Grip Diameter:**

Between 0.2485 inches and 0.2495 inches

**Internal Drive Style:**

High-torque

**Thread Diameter:**

0.250 inches

**Grip Length:**

Between 0.802 inches and 0.822 inches

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Hardness Rating:**

36.0 rockwell c and 40.0 rockwell c

**Countersink Angle:**

100.0 degrees

**Material:**

Steel comp e4340 or steel comp 4340 or steel comp 8740

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2, class 2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0