NSN 5305-01-054-8398

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-054-8398 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.318 inches and 0.368 inches **Fastener Length:** Between 1.140 inches and 1.170 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.355 inches and 0.397 inches **Grip Diameter:** Between 0.2485 inches and 0.2495 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.250 inches **Grip Length:** Between 0.802 inches and 0.822 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c **Countersink Angle:** 100.0 degrees Material: Steel comp e4340 or steel comp 4340 or steel comp 8740 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, class 2 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5305-01-054-8398

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0