Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-054-9226

| Thread Class: |
|---|
| 2a |
| Za Thread Direction: |
| |
| Right-hand |
| Thread Length: 0.250 inches |
| |
| Fastener Length: |
| 0.700 inches |
| Head Style: |
| Pan |
| Head Diameter: |
| Between 0.473 inches and 0.492 inches |
| Head Height: |
| Between 0.162 inches and 0.175 inches |
| First Diameter From Head: |
| Between 0.190 inches and 0.200 inches |
| Distance From Largest Bearing Surface Of Head To End Of First Diameter: |
| 0.450 inches |
| Internal Drive Style: |
| Cross recess type 1 |
| Thread Diameter: |
| 0.250 inches |
| Thready Qty Per Inch (tpi): |
| 28 |
| Min. Tensile Strength (psi): |
| 2910 pounds per square inch |
| Material: |
| Steel |
| Material Specification: |
| Qq-s763, class 300 federal specification single material response |
| Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response |
| Thread Series Designator: |
| Unf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| |
| |

NSN 5305-01-054-9226

Externally Relieved Body Screw - Page 2 of 2

Fiig: A003b0

