## NSN 5305-01-055-1148

Close Tolerance Screw - Page 1 of 1





View Online at https://aerobasegroup.com/nsn/5305-01-055-1148

| Thread Class:   |
|---|
| 3a  |
| Thread Direction:   |
| Right-hand  |
| Thread Length:  |
| Between 0.320 inches and 0.370 inches                                     |
| Fastener Length:  |
| Between 0.955 inches and 0.985 inches                                     |
| Head Style:   |
| Flat countersunk  |
| Head Diameter:  |
| Between 0.337 inches and 0.383 inches                                     |
| Grip Diameter:  |
| Between 0.1885 inches and 0.1895 inches                                   |
| Internal Drive Style:   |
| Cross recess type 1   |
| Thread Diameter:  |
| 0.190 inches  |
| Grip Length:  |
| Between 0.615 inches and 0.635 inches                                     |
| Thready Qty Per Inch (tpi):   |
| 32  |
| Countersink Angle:  |
| 100.0 degrees   |
| Surface Finish:   |
| 32.0 microinches threads  |
| Material:   |
| Steel comp e4340 or steel comp 4340 or steel comp 8740                    |
| Surface Treatment:  |
| Cadmium and chromate  |
| Surface Treatment Specification:  |
| Qq-p-416, type 2, class 2 federal specification single treatment response |
| Thread Series Designator:   |
| Unjf  |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A003b0  |
|   |