NSN 5305-01-055-3812

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/psp/5305-01-055-3812

View Online at https://aerobasegroup.com/nsn/5305-01-055-3812
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.552 inches and 0.602 inches
Fastener Length:
Between 1.874 inches and 1.904 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.704 inches and 0.762 inches
Grip Diameter:
Between 0.3735 inches and 0.3745 inches
Internal Drive Style:
Offset cruciform (torque set)
Thread Diameter:
0.375 inches
Grip Length:
Between 1.302 inches and 1.322 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
180000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 40.0 rockwell c
Countersink Angle:
100.0 degrees
Surface Finish:
32.0 microinches threads
Material:
Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150
Surface Treatment:
Cadmium
Surface Treatment Specification:
Nas672 assn standard all treatment responses
Thread Series Designator:
Unf
Specification Data:
80205-nas2806 professional/industrial association standard
Shelf Life:

N/a

NSN 5305-01-055-3812

Close Tolerance Screw - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0