## NSN 5305-01-055-8806

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-055-8806

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.995 inches and 1.125 inches
Fastener Length:
Between 4.000 inches and 4.120 inches
Head Style:
Flat chamfer
Head Diameter:
Between 1.723 inches and 1.750 inches
Head Height:
Between 0.735 inches and 0.750 inches
Shoulder Diameter:
1.246 inches first shoulder and 1.248 inches first shoulder
Shoulder Length:
2.995 inches first shoulder and 3.005 inches first shoulder
Single Shear Strength:
34800 pounds per square inch
Internal Drive Style:
Hexagon
Thread Diameter:
0.875 inches
Width Across Flats:
0.625 inches
Thready Qty Per Inch (tpi):
9
Min. Tensile Strength (psi):
140000 pounds per square inch
Hardness Rating:
32.0 rockwell c and 43.0 rockwell c
Shoulder Shape:
Round first shoulder
Material:
Steel
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416 ty2 cl3 federal specification single treatment response
Thread Series Designator:

Unc

## NSN 5305-01-055-8806

Shoulder Screw - Page 2 of 2



_					
•	n	<b>0</b> 1	•	12	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0