

View Online at <https://aerobasegroup.com/nsn/5305-01-056-0172>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.927 inches and 0.994 inches

**Fastener Length:**

Between 2.999 inches and 3.046 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 1.262 inches and 1.272 inches

**Grip Diameter:**

Between 0.6230 inches and 0.6240 inches

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.625 inches

**Grip Length:**

Between 2.052 inches and 2.072 inches

**Thready Qty Per Inch (tpi):**

18

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Hardness Rating:**

36.0 rockwell c and 40.0 rockwell c

**Countersink Angle:**

100.0 degrees

**Surface Finish:**

32.0 microinches grip

**Material:**

Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416 ty2 cl2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas340 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0