## NSN 5305-01-056-1502

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-056-1502 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.329 inches and 0.415 inches Fastener Length: Between 1.045 inches and 1.075 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.574 inches and 0.637 inches **Shoulder Diameter:** 0.311 inches first shoulder and 0.312 inches first shoulder **Shoulder Length:** 0.506 inches first shoulder **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** 100.0 degrees **Shoulder Shape:** Round first shoulder Material: Steel comp e4340 or steel comp 4340 or steel comp 8740 **Surface Treatment:** Cadmium and chromate esponse

Surface Treatment Specification:
Qq-p-416, type 2, class 3 federal specification single treatment re
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

## **NSN 5305-01-056-1502** Shoulder Screw - Page 2 of 2



Fiig:

A003b0