NSN 5305-01-056-1511

Close Tolerance Screw - Page 1 of 1

View Online at https://aerobasegroup.com/nsn/5305-01-056-1511



| Thread Class: |
|---|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.400 inches and 0.450 inches |
| Fastener Length: |
| Between 1.785 inches and 1.815 inches |
| Head Style: |
| Flat countersunk |
| Head Diameter: |
| Between 0.455 inches and 0.510 inches |
| Grip Diameter: |
| Between 0.2485 inches and 0.2495 inches |
| Internal Drive Style: |
| Cross recess type 1 |
| Thread Diameter: |
| 0.250 inches |
| Grip Length: |
| Between 1.365 inches and 1.385 inches |
| Thready Qty Per Inch (tpi): |
| 28 |
| Countersink Angle: |
| 100.0 degrees |
| Surface Finish: |
| 32.0 microinches threads |
| Material: |
| Steel comp e4340 or steel comp 4340 or steel comp 8740 |
| Surface Treatment: |
| Cadmium and chromate |
| Surface Treatment Specification: |
| Qq-p-416, type 2, class 2 federal specification single treatment response |
| Thread Series Designator: |
| Unjf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A003b0 |
| |