

View Online at <https://aerobasegroup.com/nsn/5305-01-056-3198>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.292 inches and 0.363 inches

Fastener Length:

Between 0.660 inches and 0.680 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.339 inches and 0.381 inches

Grip Diameter:

Between 0.1885 inches and 0.1895 inches

Internal Drive Style:

Offset cruciform (torque set)

Thread Diameter:

0.190 inches

Grip Length:

Between 0.302 inches and 0.322 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

160000 pounds per square inch

Countersink Angle:

100.0 degrees

Surface Finish:

32.0 microinches threads

Material:

Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 6150 or steel comp 8735

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification all treatment responses

Thread Series Designator:

Unjf

Specification Data:

80205-nas1580 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0