NSN 5305-01-056-3200

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-056-3200 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.490 inches and 0.542 inches **Fastener Length:** Between 1.312 inches and 1.344 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.929 inches and 1.024 inches **Grip Diameter:** Between 0.4982 inches and 0.4991 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.500 inches **Grip Length:** Between 0.802 inches and 0.822 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c **Countersink Angle:** 100.0 degrees Surface Finish: 63.0 microinches grip Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, class 3 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a

--

Unit Of Measure:

NSN 5305-01-056-3200

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0