NSN 5305-01-056-4662

Setscrew - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-056-4662

Inread	i Class:
2a	
Thread	Direction:
Right-h	hand
Thread	Length:
0.240 i	nches
Faster	er Length:
0.430 i	nches
Head S	Style:
Flat ch	amfer
Head I	Diameter:
0.265 i	nches
Head I	leight:
0.165 i	nches
Point I	_ength:
0.190 i	nches
Point I	Diameter:
Betwee	en 0.112 inches and 0.118 inches
Point \$	Style:
Flat	
Interna	al Drive Style:
Hexag	on
Thread	d Diameter:
0.164 i	nches
Width	Across Flats:
0.156 i	nches
Thread	dy Qty Per Inch (tpi):
32	
Point (Chamfer Angle:
90.0 de	egrees
Materi	al:
Stainle	ss steel
Surfac	e Treatment:
Passiv	ate
Surfac	e Treatment Specification:
Mil-f-14	1072 e300 military specification single treatment response
Thread	d Series Designator:
Unc	
Shelf I	.ife:
N/a	

--

NSN 5305-01-056-4662

Setscrew - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-f-14072 spec.

