NSN 5305-01-056-5099

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-056-5099 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.938 inches and 1.000 inches **Fastener Length:** Between 0.969 inches and 1.000 inches **Head Style:** Pan **Head Diameter:** Between 0.357 inches and 0.373 inches **Head Height:** Between 0.122 inches and 0.133 inches **Locking Feature:** Pellet or strip **Internal Drive Style:** Torque set **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 **Screw Material:** Steel comp 4140 or steel comp 4340 or steel comp 8740 **Locking Feature Material:** Plastic polychlorotrifluoroethylene **Screw Material Specification:** Mil-s-5656 military specification 1st material response or mil-s-8844 military specification 2nd material response or ams 6414 assn standard 2nd material response or mil-s-6049 military specification 3rd material response **Locking Feature Material Specification:** Ams 3650 assn standard single material response **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416, type 2, class 2 federal specification 5th treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

No

Unit Of Measure:

Demilitarization:

NSN 5305-01-056-5099

Machine Screw - Page 2 of 2



Fiig:

A500d0

Mil-std (military Standard):

Mil-s-5656 spec.