## NSN 5305-01-056-5435

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-056-5435 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.150 inches **Fastener Length:** Between 0.470 inches and 0.500 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.256 inches and 0.270 inches **Head Height:** Between 0.087 inches and 0.097 inches **First Diameter From Head:** 0.350 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.079 inches and 0.084 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Stainless steel **Surface Treatment:** Oxide **Surface Treatment Specification:** Mil-c-13924, class 3 military specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No

Fiig:

A003b0

## NSN 5305-01-056-5435

Externally Relieved Body Screw - Page 2 of 2



Mil-std (military Standard):

Mil-c-13924 spec.