

View Online at <https://aerobasegroup.com/nsn/5305-01-057-3742>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.414 inches and 0.500 inches

Fastener Length:

Between 0.470 inches and 0.500 inches

Head Style:

Flat chamfer

Head Diameter:

Between 0.262 inches and 0.270 inches

Head Height:

Between 0.159 inches and 0.164 inches

Internal Drive Style:

Hexagon

Thread Diameter:

0.164 inches

Width Across Flats:

Between 0.140 inches and 0.142 inches

Thready Qty Per Inch (tpi):

36

Min. Tensile Strength (psi):

180000 pounds per square inch

Hardness Rating:

38.0 rockwell c and 45.0 rockwell c

Minimum Yield Strength:

155000 pounds per square inch

Special Features:

Finish color black

Material:

Steel

Surface Treatment:

Oxide

Surface Treatment Specification:

Mil-c-13924, cl1 military specification single treatment response

Thread Series Designator:

Unrf

Specification Data:

80205-nas1351 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.