## NSN 5305-01-057-4244

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-057-4244 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.210 inches **Fastener Length:** Between 0.300 inches and 0.350 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.300 inches and 0.327 inches **Head Height:** Between 0.076 inches and 0.086 inches **Hole Diameter:** Between 0.046 inches and 0.050 inches First Diameter From Head: Between 0.089 inches and 0.099 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.090 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.138 inches **Hole Quantity: Hole Type:** Drilled Thready Qty Per Inch (tpi): 32 **Hole Configuration Style: Externally Relieved Body Diameter Quantity:** Material: Steel comp 303 **Material Specification:** Astm a582 assn standard single material response **Surface Treatment:** Cadmium

**Surface Treatment Specification:** 

Qq-p-416, type 2, class 3 federal specification single treatment response

## NSN 5305-01-057-4244

Externally Relieved Body Screw - Page 2 of 2



Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A003b0