

View Online at <https://aerobasegroup.com/nsn/5305-01-057-8126>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.420 inches and 0.500 inches

Fastener Length:

Between 0.470 inches and 0.500 inches

Head Style:

Flat chamfer

Head Diameter:

Between 0.176 inches and 0.183 inches

Head Height:

Between 0.108 inches and 0.112 inches

Locking Feature:

Strip threads

Internal Drive Style:

Hexagon

Thread Diameter:

0.112 inches

Width Across Flats:

Between 0.0937 inches and 0.0952 inches

Thready Qty Per Inch (tpi):

40

Min. Tensile Strength (psi):

80000 pounds per square inch

Hardness Rating:

80.0 rockwell b

Minimum Yield Strength:

30000 pounds per square inch

Material:

Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 or steel comp xm-7

Material Specification:

66 federal standard 1st material response or 66 federal standard 2nd material response or 66 federal standard 3rd material response or 66 federal standard 4th material response or 66 federal standard 5th material response or astm a493 assn standard 6th material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unrc

Specification Data:

80205-nas 1352 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0