
NSN 5305-01-057-8140

Close Tolerance Screw - Page 1 of 2





Thread Class:
За
Thread Direction:
Right-hand
Thread Length:
Between 0.291 inches and 0.341 inches
Fastener Length:
Between 0.863 inches and 0.893 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.350 inches and 0.399 inches
Grip Diameter:
Between 0.2485 inches and 0.2495 inches
Internal Drive Style:
High-torque
Thread Diameter:
0.250 inches
Grip Length:
Between 0.552 inches and 0.572 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 40.0 rockwell c
Countersink Angle:
100.0 degrees
Surface Finish:
63.0 microinches threads
Material:
Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740 or steel comp 4130
Surface Treatment:
Nickel and cadmium
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

NSN 5305-01-057-8140

Close Tolerance Screw - Page 2 of 2

Fiig: A003b0

