NSN 5305-01-057-8146

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-057-8146

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.338 inches and 0.388 inches
Fastener Length:
Between 1.160 inches and 1.190 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.339 inches and 0.381 inches
Grip Diameter:
Between 0.1885 inches and 0.1895 inches
Internal Drive Style:
Offset cruciform (torque set)
Thread Diameter:
0.190 inches
Grip Length:
Between 0.802 inches and 0.822 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
160000 pounds per square inch Hardness Rating:
Hardness Rating:
Hardness Rating: 36.0 rockwell c and 40.0 rockwell c
Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Countersink Angle:
Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Countersink Angle: 100.0 degrees
Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Countersink Angle: 100.0 degrees Surface Finish:
Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches threads
Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches threads Material:
Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches threads Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 6150 or steel comp 8735
Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches threads Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 6150 or steel comp 8735 Surface Treatment:
Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches threads Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 6150 or steel comp 8735 Surface Treatment: Cadmium and chromate
Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches threads Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 6150 or steel comp 8735 Surface Treatment: Cadmium and chromate Surface Treatment Specification:
Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches threads Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 6150 or steel comp 8735 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416 ty2 cl2 federal specification single treatment response
Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches threads Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 6150 or steel comp 8735 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416 ty2 cl2 federal specification single treatment response Thread Series Designator:
Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches threads Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 6150 or steel comp 8735 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416 ty2 cl2 federal specification single treatment response Thread Series Designator: Unjf

N/a

NSN 5305-01-057-8146

Close Tolerance Screw - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0