## NSN 5305-01-057-9328

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-057-9328

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.337 inches and 0.387 inches
Fastener Length:
Between 0.534 inches and 0.564 inches
Head Style:
Pan no. 2
Head Diameter:
Between 0.360 inches and 0.374 inches
Head Height:
Between 0.115 inches and 0.125 inches
Grip Diameter:
Between 0.1885 inches and 0.1895 inches
Internal Drive Style:
Offset cruciform (torque set)
Thread Diameter:
0.190 inches
Grip Length:
Between 0.178 inches and 0.198 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 40.0 rockwell c
Surface Finish:
32.0 microinches threads
Special Features:
Internal drive ribbed
Material:
Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 6150 or steel comp 8735
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416 ty2 cl2 federal specification single treatment response
Thread Series Designator:
Unjf
Specification Data:

80205-nas1578 professional/industrial association standard

## NSN 5305-01-057-9328

Close Tolerance Screw - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J	116		_	.II C.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0