## NSN 5305-01-057-9339

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-057-9339

View Online at https://aerobasegroup.com/nsn/5305-01-057-9339					
Thread Class:					
3a					
Thread Direction:					
Right-hand					
Thread Length:					
Between 0.378 inches and 0.428 inches					
Fastener Length:					
Between 1.326 inches and 1.356 inches					
Head Style:					
Flat countersunk					
Head Diameter:					
Between 0.464 inches and 0.507 inches					
Grip Diameter:					
Between 0.2485 inches and 0.2495 inches					
Internal Drive Style:					
Offset cruciform (torque set)					
Thread Diameter:					
0.250 inches					
Grip Length:					
Between 0.928 inches and 0.948 inches					
Thready Qty Per Inch (tpi):					
28					
Min. Tensile Strength (psi):					
160000 pounds per square inch					
Hardness Rating:					
36.0 rockwell c and 40.0 rockwell c					
Countersink Angle:					
Between 99.0 degrees and 101.0 degrees					
Surface Finish:					
32.0 microinches threads					
Material:					
Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150					
Surface Treatment:					
Cadmium and chromate					
Surface Treatment Specification:					
Qq-p-416 type 2 cl 2 federal specification single treatment response					
Thread Series Designator:					
Unjf					
Specification Data:					
80205-nas1580 professional/industrial association standard					
Shelf Life:					

N/a

## NSN 5305-01-057-9339

Close Tolerance Screw - Page 2 of 2



		• •			
ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0