
## NSN 5305-01-058-0751

Close Tolerance Screw - Page 1 of 2

---





Thread Class:
За
Thread Direction:
Right-hand
Thread Length:
Between 0.650 inches and 0.700 inches
Fastener Length:
Between 1.285 inches and 1.315 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.605 inches and 0.674 inches
Grip Diameter:
Between 0.4360 inches and 0.4370 inches
Internal Drive Style:
Offset cruciform (torque set)
Thread Diameter:
0.438 inches
Grip Length:
Between 0.615 inches and 0.635 inches
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 40.0 rockwell c
Countersink Angle:
100.0 degrees
Surface Finish:
32.0 microinches threads
Material:
Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740
Surface Treatment:
Cadmium and chromate
Thread Series Designator:
Unjf
Specification Data:
80205-nas1581 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:

## NSN 5305-01-058-0751

Close Tolerance Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

