NSN 5305-01-058-3316

Demilitarization:

No Fiig: A500d0



Machine Screw - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5305-01-058-3316 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.512 inches and 0.574 inches **Fastener Length:** Between 0.594 inches and 0.625 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.147 inches and 0.172 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.086 inches Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi): 55000 pounds per square inch **Countersink Angle:** 82.0 degrees **Screw Material:** Copper alloy 230 or copper alloy 240 or copper alloy 260 or copper alloy 268 or copper alloy 342 or copper alloy 353 or copper alloy 360 or copper alloy 377 or copper alloy 270 or copper alloy 510 or copper alloy 745 or copper alloy 752 or copper alloy 770 **Screw Surface Treatment:** Nickel **Thread Series Designator:** Unc **Specification Or Standard:** 3 type and 2c style **Departure From Cited Document:** As modified by surface finish Shelf Life: N/a **Unit Of Measure:**