## NSN 5305-01-058-3880

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-058-3880 **Thread Class:** 2a **Thread Direction:** Right-hand Fastener Length: Between 0.292 inches and 0.312 inches **Head Style:** Pan **Head Diameter:** Between 0.205 inches and 0.219 inches **Head Height:** Between 0.070 inches and 0.080 inches Washer Quantity: **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): **Secondary Washer Relationship To Primary Washer:** Not identical **Secondary Washer Style:** Flat **Primary Washer Outside Diameter:** Between 0.195 inches and 0.208 inches **Secondary Washer Outside Diameter:** Between 0.245 inches and 0.250 inches **Primary Washer Style:** Split helical ring **Primary Washer Material Thickness:** 0.031 inches **Secondary Washer Material Thickness:** Between 0.017 inches and 0.025 inches Material: Steel comp 1008 or steel comp 1010 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 **Surface Treatment:** Cadmium and chromate or cadmium **Thread Series Designator:** Unc

N/a

Shelf Life:

## NSN 5305-01-058-3880

Assembled Washer Screw - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0