## NSN 5305-01-058-3886

3a

32

N/a

---

Socket Head Cap Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-058-3886



## **Thread Class: Thread Direction: Right-hand Thread Length:** Between 0.157 inches and 0.250 inches Fastener Length: Between 0.219 inches and 0.250 inches **Head Style:** Pan **Head Diameter:** Between 0.306 inches and 0.322 inches **Head Height:** Between 0.105 inches and 0.115 inches Locking Feature: Pellet threads or strip threads **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Iron alloy 660 **Material Specification:** Ams 5737 assn standard single material response **Surface Treatment:** Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjc **Specification Data:** 80205-nas1190 professional/industrial association standard Shelf Life: Unit Of Measure:

## NSN 5305-01-058-3886

Socket Head Cap Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

