NSN 5305-01-058-3918

Shoulder Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-058-3918

| Thread Class: |
|---|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.390 inches |
| Fastener Length: |
| 1.810 inches |
| Head Style: |
| Flat chamfer |
| Head Diameter: |
| Between 0.616 inches and 0.621 inches |
| Head Height: |
| 0.370 inches |
| Shoulder Diameter: |
| 0.368 inches first shoulder and 0.371 inches first shoulder |
| Shoulder Length: |
| 1.340 inches first shoulder |
| Internal Drive Style: |
| Slot |
| Thread Diameter: |
| 0.312 inches |
| Thready Qty Per Inch (tpi): |
| 24 |
| Hardness Rating: |
| 26.0 rockwell c and 32.0 rockwell c |
| Shoulder Shape: |
| Round first shoulder |
| Special Features: |
| Dry film lubricant |
| Material: |
| Steel comp 4130 or steel comp e4340 or steel comp 4340 |
| Thread Series Designator: |
| Unjf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A003b0 |