NSN 5305-01-058-3921

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-058-3921

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.378 inches and 0.428 inches
Fastener Length:
Between 1.138 inches and 1.168 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.350 inches and 0.399 inches
Grip Diameter:
Between 0.2485 inches and 0.2495 inches
Internal Drive Style:
Offset cruciform (torque set)
Thread Diameter:
0.250 inches
Grip Length:
Between 0.740 inches and 0.760 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
160000 pounds per square inch
160000 pounds per square inch Hardness Rating:
Hardness Rating:
Hardness Rating: 36.0 rockwell c and 40.0 rockwell c
Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Countersink Angle:
Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Countersink Angle: 100.0 degrees
Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Countersink Angle: 100.0 degrees Surface Finish:
Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches threads
Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches threads Material:
Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches threads Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 6150 or steel comp 8735
Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches threads Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 6150 or steel comp 8735 Surface Treatment:
Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches threads Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 6150 or steel comp 8735 Surface Treatment: Cadmium and chromate
Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches threads Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 6150 or steel comp 8735 Surface Treatment: Cadmium and chromate Surface Treatment Specification:
Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches threads Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 6150 or steel comp 8735 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416 ty2 cl2 federal specification single treatment response
Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches threads Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 6150 or steel comp 8735 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416 ty2 cl2 federal specification single treatment response Thread Series Designator:
Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches threads Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 6150 or steel comp 8735 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416 ty2 cl2 federal specification single treatment response Thread Series Designator: Unjf

N/a

NSN 5305-01-058-3921

Close Tolerance Screw - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A003b0