## NSN 5305-01-058-3933

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-058-3933

Thread Cla	SS:
3a	
Thread Dire	ection:
Right-hand	
Thread Len	igth:
Between 0.3	337 inches and 0.387 inches
Fastener Lo	ength:
Between 0.8	534 inches and 0.564 inches
Head Style:	
Flat counter	sunk
Head Diam	eter:
Between 0.3	339 inches and 0.381 inches
Grip Diame	ter:
Between 0.7	1885 inches and 0.1895 inches
Internal Dri	ve Style:
Offset crucif	form (torque set)
Thread Dia	meter:
0.190 inche	S
Grip Lengtl	h:
Between 0.7	177 inches and 0.197 inches
Thready Qt	y Per Inch (tpi):
32	
Min. Tensil	e Strength (psi):
160000 pou	nds per square inch
Countersin	k Angle:
100.0 degre	es
Surface Fir	lish:
32.0 microir	iches threads
Material:	
Iron alloy 66	50
Material Sp	ecification:
Ams 5731 a	ssn standard single material response or ams 5732 assn standard single material response or ams 5737 assn standard single
material res	ponse
Surface Tre	eatment:
Cadmium a	ind chromate
Surface Tre	eatment Specification:
Qq-p-416 ty	pe 2 cl 2 federal specification single treatment response
Thread Ser	ies Designator:
Unjf	
Specificatio	on Data:
80205-nas1	580 professional/industrial association standard
Shelf Life:	

N/a

## NSN 5305-01-058-3933

Close Tolerance Screw - Page 2 of 2

AeroBase Group

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0