## NSN 5305-01-058-3934

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-058-3934

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.743 inches and 0.793 inches
Fastener Length:
Between 1.753 inches and 1.783 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.951 inches and 1.014 inches
Grip Diameter:
Between 0.4985 inches and 0.4995 inches
Internal Drive Style:
Offset cruciform (torque set)
Thread Diameter:
0.500 inches
Grip Length:
Between 0.990 inches and 1.010 inches
Thready Qty Per Inch (tpi):
20 Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 40.0 rockwell c
Countersink Angle:
100.0 degrees
Surface Finish:
32.0 microinches threads
Material:
Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416 ty2 cl2 federal specification single treatment response
Thread Series Designator:
Unjf
-
Specification Data: 80205-nas1580 professional/industrial association standard
Shelf Life:
N/a

## NSN 5305-01-058-3934

Close Tolerance Screw - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0