NSN 5305-01-058-4633

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-058-4633

Thread Class:	
За	
Thread Direction:	
Right-hand	
Thread Length:	
Between 0.378 inches and 0.428 inches	
Fastener Length:	
Between 0.888 inches and 0.918 inches	
Head Style:	
Flat countersunk	
Head Diameter:	
Between 0.350 inches and 0.399 inches	
Grip Diameter:	
Between 0.2485 inches and 0.2495 inches	
nternal Drive Style:	
Offset cruciform (torque set)	
Thread Diameter:	
0.250 inches	
Grip Length:	
Between 0.490 inches and 0.510 inches	
Thready Qty Per Inch (tpi):	
28	
Min. Tensile Strength (psi):	
160000 pounds per square inch	
Countersink Angle:	
100.0 degrees	
Surface Finish:	
32.0 microinches threads	
Material:	
ron alloy 660	
Material Specification:	
Ams 5731 assn standard single material response or ams 5732 assn standard single material response or ams 5737 assn standard	single
naterial response	
Surface Treatment:	
Passivate	
Surface Treatment Specification:	
Qq-p-35 federal specification single treatment response	
Thread Series Designator:	
Jnjf	
Specification Data:	
30205-nas1581 professional/industrial association standard	
Shelf Life:	

N/a

NSN 5305-01-058-4633

Close Tolerance Screw - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0