## NSN 5305-01-058-7067

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-058-7067 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.317 inches and 0.369 inches **Fastener Length:** Between 0.578 inches and 0.610 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.329 inches and 0.388 inches **Grip Diameter:** Between 0.1885 inches and 0.1894 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches **Grip Length:** Between 0.241 inches and 0.261 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c **Countersink Angle:** 100.0 degrees Surface Finish: 63.0 microinches grip Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, class 3 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 5305-01-058-7067

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0