NSN 5305-01-058-8432

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-058-8432

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.489 inches and 0.541 inches
Fastener Length:
Between 1.687 inches and 1.719 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.929 inches and 1.024 inches
Grip Diameter:
Between 0.4982 inches and 0.4991 inches
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.500 inches
Grip Length:
Between 1.178 inches and 1.198 inches
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 40.0 rockwell c
Countersink Angle:
100.0 degrees
Surface Finish:
63.0 microinches grip
Material:
Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740
Surface Treatment:
Cadmium and chromate
Confess Treatment Consideration.
Surface Treatment Specification:
Qq-p-416, type 2, class 3 federal specification single treatment response
Qq-p-416, type 2, class 3 federal specification single treatment response
Qq-p-416, type 2, class 3 federal specification single treatment response Thread Series Designator:
Qq-p-416, type 2, class 3 federal specification single treatment response Thread Series Designator: Unf

N/a

NSN 5305-01-058-8432

Close Tolerance Screw - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A003b0