NSN 5305-01-059-0228

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-059-0228 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.735 inches and 0.802 inches **Fastener Length:** Between 6.120 inches and 6.167 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.950 inches and 1.017 inches **Grip Diameter:** Between 0.4982 inches and 0.4991 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.500 inches **Grip Length:** Between 5.365 inches and 5.385 inches Thready Qty Per Inch (tpi): 20 **Hardness Rating:** 46.0 rockwell c and 50.0 rockwell c **Countersink Angle:** 100.0 degrees **Surface Finish:** 32.0 microinches grip **Product Name:** Navy special project Material: Steel comp h11 **Material Specification:** Ams 6487 assn standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Mil-c-8837 type 2 cl 2 military specification single treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a

NSN 5305-01-059-0228

Close Tolerance Screw - Page 2 of 2



| П | Init | 7 1+ | Measure: |
|---|-------|------|-----------|
| u | ,,,,, | v | wicasuic. |

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.